

- [7] H. Kurama, I.B. Topçu, C. Karakurt, "Properties of autoclaved aerated concrete produced from coal bottom ash," *Journal of Materials Processing Technology*, vol. 209, pp. 767–773, 2009.
- [8] S. Goñi, A. Guerero, M.P. Luxán, A. Macías, "Activation of the fly ash pozzolanic reaction by hydrothermal conditions," *Cement and Concrete Research*, vol. 33, pp. 1399–1405, 2003.
- [9] N. Narayanan, K. Ramamurthy, "Microstructural investigation on aerated concrete," *Cement and Concrete Research*, vol. 30, pp. 457–464, 2000.
- [10] J. Kikuma, M. Tsunashima, T. Ishikawa, S. Matsuno, A. Ogawa, K. Matsui, M. Sato, "Effects of quartz particle size and water-to-solid ratio on hydrothermal synthesis of tobermorite studied by in-situ time-resolved X-ray diffraction," *Journal of Solid State Chemistry*, vol. 184, pp. 2066–2074, 2011.
- [11] D.S. Klimesch, A. Ray, "Effects of quartz particle size on hydrogarnet formation during autoclaving at 180 °C in the CaO-Al₂O₃-SiO₂-H₂O system," *Cement and Concrete Research*, vol. 28, pp. 1309–1316, 1998.
- [12] N. Isu, H. Ishida, T. Mitsuda, "Influence of quartz particle size on the chemical and mechanical properties of autoclaved aerated concrete (I) tobermorite formation," *Cement and Concrete Research*, vol. 25, pp. 243–248, 1995.
- [13] E., Venhodová, "Development of tobermorite in aerated concrete depending on the length of autoclaving", 16th International Conference of PhD Students, JUNIORSTAV: 4.1 Physical and chemical properties of building materials, Brno University of Technology, Faculty of Civil Engineering, p. 313, 2014, ISBN 978-80-214-4851-3.
- [14] K., Baltakys, R. Siauciunas, „The influence of γ -Al₂O₃ and Na₂O on the formation of calcium silicate hydrates in the CaO – quartz – H₂O system“, *Materials Science-Poland*, vol. 25, No. 1, pp. 185–198, 2007.